United States Patent [19]

Reynolds et al.

Patent Number: [11]

4,474,446

Date of Patent:

Oct. 2, 1984

[54]	FOCAL SENSOR HAVING OPTICAL LOW PASS FILTER		
[75]	Inventors:	George O. Reynolds, Waban; Burton R. Clay, Wayland, both of Mass.	
[73]	Assignee:	Honeywell Inc., Minneapolis, Minn.	
[21]	Appl. No.:	393,565	
f 3	Filed:	Jun. 30, 1982	
[51]	Int. Cl.3	G03B 7/08; G01J 1/42;	
[52]	U.S. Cl. 250	G02B 5/18; G02B 5/20 354/402; 354/479; /204; 250/237 G; 350/311; 350/162.24	

[58] Field of Search 354/25 R, 25 A, 25 N, 354/25 P, 31 F, 59, 402-409, 479, 482; 250/201, 204, 237 R, 237 G; 350/311, 314, 162.11,

162.15, 162.16, 162.24 [56]

References Cited

U.S. PATENT DOCUMENTS

3,402,001	9/1968	Fleisher 350/162.24 X
3,631,360	12/1971	Lehovec 350/162.16 X
3 904 869	9/1975	Stauffer 354/25 X
4 048 492	9/1977	Hartmann 250/237 G
4,132,888	1/1979	Kondo 354/25 X

4,247,763 1/1981 Stauffer 350/314 X

FOREIGN PATENT DOCUMENTS

2082335 3/1982 United Kingdom 250/201

OTHER PUBLICATIONS

"Electronic Focus for Cameras", Stauffer et al., Scientific Honeyweller, vol. 3, No. 1, Mar. 1982, pp. 1-13.


Primary Examiner-William B. Perkey

Attorney, Agent, or Firm-John S. Solakian; Laurence J. Marhoefer

ABSTRACT

A system having a scaled anti-aliasing random phase filter for use in optical imaging systems having a sampled focal plane or an automatic focussing device. The filter is scaled so that it may be placed near the focal plane or automatic focus sensing device, yet produce the effect of an anti-aliasing filter at the exit pupil of the optical system. In one example, the filter includes a scaled hologram of a Sayanagi filter located at the exit pupil. In a second example, the filter includes a scaled double chirped diffraction grating.

20 Claims, 5 Drawing Figures






FIG. 2